


STEELMARK

AHS™



GOODYEAR


- Decoupling groove to reduce erratic free rolling wear
- 5-rib design for even tread wear and traction on wet road conditions
- 18/32" tread depth
- Improved tire cavity minimizes stress and improves casing integrity and retreadability
- 3-Full belts to protect the radial casing and provide tread area reinforcement

Steelmark Tire Name	Tire Size	Tread Depth (32nds")	Goodyear Product Code	Load Range	Single Load (LBS)	Single Inflation (PSI)	Dual Load (LBS)	Dual Inflation (PSI)
AHS™	11R24.5	18	358798420	H	6,610	110	6,005	110
AHS™	11R22.5	18	358799420	H	6,175	110	5,840	110
AHS™	295/75R22.5	18	358938420	G	6,175	105	5675	105
AHS™	285/75R24.5	18	358940420	G	6,175	105	5675	105
AHS™	11R22.5	18	358953420	G	6,175	105	5,840	105
AHS™	11R24.5	18	358955420	G	6,610	105	6,005	105

Wingfoot Commercial Tire Systems, LLC

STEELMARK

AHD II™



- Closed shoulders for improved over the highway tread life and low tire noise, while maintaining good wet or dry traction with 11-sided lug elements
- 26/32: tread depth for increased resistance to irregular wear on single and tandem axle tractors
- Fuel-efficient casing design -optimized casing profile delivers outstanding, fleet proven mileage on trailer axles
- High-tensile steel bead provides easier mounting

Steelmark Tire Name	Tire Size	Tread Depth (32nds")	Goodyear Product Code	Load Range	Single Load (LBS)	Single Inflation (PSI)	Dual Load (LBS)	Dual Inflation (PSI)
AHDII™	295/75R22.5	28	358603419	G	6,175	110	5,675	100
AHDII™	285/75R24.5	28	358604419	G	6,175	110	5,675	100
AHDII™	11R22.5	28	358953419	G	6,175	105	5,840	105
AHDII™	11R24.5	28	358955419	G	6,610	105	6,005	105




Wingfoot Commercial Tire Systems, LLC

STEELMARK

AHD™

Limited Availability




- Open shoulders for increased on and off-highway traction
- 26/32: tread depth for improved tread wear and puncture resistance
- Twin centerline riding ribs for improved on-highway handling
- 8-sided lug pattern to provide increased lateral and directional traction on wet or dry surfaces

Steelmark Tire Name	Tire Size	Tread Depth (32nds")	Goodyear Product Code	Load Range	Single Load (LBS)	Single Inflation (PSI)	Dual Load (LBS)	Dual Inflation (PSI)
AHD™	11R22.5	26	358807507	H	6,610	120	6,005	120
AHD™	11R24.5	26	358941507	H	7,160	120	6,610	120
AHD™	285/75R24.5	26	358940507	G	6,175	110	5,675	100
AHD™	295/75R22.5	26	358938507	G	6,175	110	5,675	100

Wingfoot Commercial Tire Systems, LLC

STEELMARK

AHT II™



GOODYEAR


- For over the highway use in trailer position
- Shallow 13/32" tread depth for increased resistance to irregular wear on free - rolling axle positions
- Fuel-efficient casing design -optimized casing profile delivers outstanding, fleet proven mileage on trailer axles
- High-tensile steel bead provides easier mounting

Steelmark Tire Name	Tire Size	Tread Depth (32nds")	Goodyear Product Code	Load Range	Single Load (LBS)	Single Inflation (PSI)	Dual Load (LBS)	Dual Inflation (PSI)
AHT II™	295/75R22.5	13	358938506	G	6,175	110	5,675	100
AHT II™	285/75R24.5	13	358940506	G	6,175	110	5,675	100
AHT II™	11R22.5	13	358953508	G	6,175	105	5,840	105
AHT II™	11R24.5	13	358955508	G	6,610	105	6,005	105

Wingfoot Commercial Tire Systems, LLC

STEELMARK

AHR II™



- For all position use in size 255/70R22.5
- 18/32" tread depth for increased resistance to irregular wear on free - rolling axle positions
- Fuel-efficient casing design -optimized casing profile delivers outstanding, fleet proven mileage on trailer axles
- High-tensile steel bead provides easier mounting

Steelmark Tire Name	Tire Size	Tread Depth (32nds")	Goodyear Product Code	Load Range	Single Load (LBS)	Single Inflation (PSI)	Dual Load (LBS)	Dual Inflation (PSI)
AHR II™	255/70R22.5	18	358780050	H	5,510	120	5,070	120

Wingfoot Commercial Tire Systems, LLC