

UNISTEEL® G647 RSS®

Goodyear's Newest All-Position Regional Tire Provides Even Wear And Long Tread Life

- Circumferential grooves and lateral blading provide excellent wet traction capability
- Raised sidewall protector ribs help to increase resistance to sidewall damage
- 360° wear indicators within sidewall protector ribs give early detection of sidewall wear/curbing damage around tire
- Mud and snow rated

TIRE SIZE	LOAD RANGE	TREAD DEPTH 32NDS INCH	DESIGN RIM WIDTH	MINIMUM DUAL SPACING IN [MM]	INFLATED DIMENSIONS				
					OVERALL WIDTH IN [MM]	OVERALL DIAMETER IN [MM]	STATIC LOADED RADIUS IN [MM]		
TUBELESS TIRES ON 5° DROP CENTER RIMS									
LT215/85R16	E	14.5	6.00	9.9 [251]	8.6 [218]	30.5 [775]	14.2 [361]		
LT225/75R16	E	14.5	6.00	10.2 [259]	8.7 [221]	29.4 [747]	13.7 [348]		
TUBELESS TIRES ON 15° DROP CENTER RIMS									
225/70R19.5	F	16.5	6.75	10.0 [254]	8.9 [226]	32.2 [818]	15.0 [381]		
245/70R19.5	F	16.5	7.50	11.0 [279]	9.5 [241]	33.2 [843]	15.4 [391]		
245/70R19.5	G	16.5	7.50	11.0 [279]	9.5 [241]	33.2 [843]	15.4 [391]		

TIRE SIZE	REVS PER MILE [KM]	TIRE WEIGHT LB [KG]	MAXIMUM LOAD @ INFLATION								SPEED RATING (MPH)
			SINGLE				DUAL				
			LBS	PSI	[KG	KPa]	LBS	PSI	[KG	KPa]	
TUBELESS TIRES ON 5° DROP CENTER RIMS											
LT215/85R16	676 [420]	52 [24]	2680	80	[1215	550]	2470	80	[1120	550]	75
LT225/75R16	701 [352]	51 [23]	2680	80	[1215	550]	2470	80	[1120	550]	75
TUBELESS TIRES ON 15° DROP CENTER RIMS											
225/70R19.5	640 [398]	63 [29]	3640	95	[1650	660]	3415	95	[1550	660]	75
245/70R19.5	626 [389]	71 [32]	4080	85	[1850	590]	3970	85	[1800	590]	75
245/70R19.5	626 [389]	76 [34]	4540	100	[2060	690]	4410	100	[2000	690]	75

Steel/Steel Construction

CLASS A, B & C

