

WRANGLER® HT

Quietest All-Weather Touring Wrangler

- Circumferential grooves provide dependable wet-weather traction
- Two-ply radial polyester cord body offers comfortable driving and positive steering response

TIRE SIZE	LOAD RANGE	TREAD DEPTH (32s)	APPRVD. RIM WIDTHS	MEAS. RIM WIDTH	NEW TIRE WIDTH	OUTSIDE DIAMETER	TREAD WIDTH	STATIC LOADED RADIUS	REVS PER MILE	MAX. LOAD AT INFLA. (PSI) SINGLE
185R14	C	10	5.0 - 6.0	5.50	7.5	25.6	5.2	11.9	811	1710@55
LT215/75R15	D	13	5.5 - 7.0	6.00	8.7	27.8	6.2	12.3	755	2095@65
LT235/75R15	C	14	6.0 - 7.0	6.50	9.3	28.9	6.8	13.3	718	1985@50
LT225/75R16	E	13	6.0 - 7.0	6.00	8.8	29.2	6.5	13.5	711	2680@80
LT245/75R16	E	13	6.5 - 7.5	7.00	9.8	30.4	7.2	14.0	683	3042@80
LT215/85R16	D	13	5.5 - 7.0	6.00	8.5	30.4	6.2	14.0	683	2335@65
LT215/85R16	E	13	5.5 - 7.0	6.00	8.5	30.4	6.2	14.0	683	2680@80
LT235/85R16	E	13	6.0 - 7.0	6.50	9.2	31.5	6.8	14.5	659	3042@80
7.50R16	D	15	5.5 - 7.0	6.00	8.6	31.8	5.0	14.6	653	2440@65

*Max. load stamped on tire sidewall reduced by 10% in accordance with federal regulation requirement for passenger tires used on light truck and multi-purpose passenger vehicles.

Fabric/Steel Construction

CLASS B & C, 5TH WHEEL, TRAVEL TRAILER

